

LUXING



PX-A6

Mini Compact Size 84x48x25mm

Charging with USB cable 5V DC or 220V AC

- Scan Mode: Carrier/Time/Search
- Busy Channel Lockout: Carrier/CTCSS/DCS
- VOX Sensitivity: 0-9 level adjustable
- Output Power: 0.5W(PMR)/ 2W (Professional)
- TOT: 0-270 selectable
- 50 CTCSS and 104 DCS
- Channel Step: 5Khz/6.25Khz/12.5Khz/25Khz
- DC 3.7V single Li-Ion battery compatible with mobile phone battery



GENERAL	
Frequency Range	400-470MHz
Operating Voltage	-20°C~+50°C
Operate Mode	Simplex or Semi-duplex
Dimension	84mm x 48mm x 25mm(Not included antenna)
Weight	130g(Including battery)
Antenna Impedance	50 Ω
TRANSMITTER	
Frequency Stability	± 2.5PPM
Output Power	UHF 2W
Max Frequency Deviation	±5KHz
Audio Distortion	≤3%
Modulation Character	+3dB~-3dB
Adjacent Channel Power	≥70dB
Spurious Radiation	≤7.5uW
Occupied Bandwidth	≤16KHz
RECEIVER	
RF Sensitivity	<0.2uV
Audio Distortion	≤3%
Audio Response	+2dB~-10dB
Co-Channel Rejection	≥-8dB
Adjacent Channel Selectivity	≥60dB
Intermodulation Rejection	≥65dB
Spurious Response	≥70dB
Blocking	≥80dB

STANDARD ACCESSORIES



FC CE 0678 RoHS ISO9001:2000

LIXING

Xiamen Puxing Electronics Science&Technology Co.,Ltd.
 ADD:No.11 Xianghong Road, Torch Gaoxin Zone,
 Xiang'an District, Xiamen, Fujian, China
 E-mail:sales@pxdz.com